2002 *FPJ* SUBJECT AND AUTHOR INDEX

All of the articles in the 2002 *Forest Products Journal*, volume 52, are listed both by subject and by author. Reprints of most articles are available at $6 each. Bulk rates are also available. Please give reprint numbers when ordering. When printer-quality reprints are no longer available, photocopies can be ordered at 50 cents per page. All orders are subject to a $6 minimum charge plus $5 handling charge per order. There is a charge of $6 for a copy of the 2002 *FPJ* Subject and Author Index.

ADHESIVES/ADHESION

Effects of Treatment Methods on Relative Reactivity of BioMass Extracts Toward Formaldehyde, C.-M. Chen and L.C.-Y. Hsu, 2:92-99 (No. 9210).

Performance of Pyrolysis Oil-Based Wood Adhesives in OSB, F. Chan, B. Riedl, X.-M. Wang, X. Lu, C. Amen-Chen, and C. Roy, 4:31-38 (No. 9230).

AIR AND WATER QUALITY

Environmental Tradeoffs: Life Cycle Approach to Evaluate the Burdens and Benefits of Emission Control Systems in the Wood Panel Industry, B. Sauer, W. Franklin, R. Miner, D. Word, and B. Upton, 3:50-59 (No. 9408).

Volatile Organic Compound Emissions During Hot-Pressing of Southern Pine Particleboard: Panel Size Effects and Trade-Off Between Press Time and Temperature, W. Wang, D.J. Gardner, and M.G.D. Baumann, 4:24-30 (No. 9261).

ANATOMY AND QUALITY

Selected Properties of Hybrid Poplar Clear Wood and Composite Panels, J.J. Peters, D.A. Bender, M.P. Wolcott, and J.D. Johnson, 5:45-54 (No. 9258).

Volume Recovery, Grade Yield, and Properties of Lumber From Young-Growth Sitka Spruce and Western Hemlock in Southeast Alaska, G.A. Christiansen, K.R. Julin, R.J. Ross, and S. Willits, 5:81-87 (No. 9226).

CHEMISTRY AND CHEMICAL MODIFICATION

Effect of Glycol on Movement of Borate From Fused Borate Rods, C.M. Freitag and J.J. Morrell, 6:68-74 (No. 9269).

COMPOSITES AND ENGINEERED PRODUCTS

Demonstration Building Constructed With Round Mortise and Tenon Joints and Salvage Material From Small-Diameter Tree Stems, C. Eckelman, H. Akcay, R. Leavitt, and E. Haviarova, 11/12:82-86 (No. 9331).

Durability of an Extruded HDPE/Wood Composite, D.E. Pendleton, T.A. Hoffard, T. Adcock, B. Woodward, and M.P. Wolcott, 6:21-27 (No. 9278).

Effect of Cement/Wood Ratio on the Properties of Cement-Bonded Particleboard Using CCA-Treated Wood Removed From Service, Y. Zhou and D.P. Kamdem, 3:77-81 (No. 9257).

The Effect of Lab-Made Flakes on Physical and Mechanical Property Variability of Laboratory Flakeboard, C.J. Moriarty, 2:69-73 (No. 9165).

Effect of Log Storage on Structural Veneer Processing, R. Shmulsky, 4:82-84 (No. 9233).

Effects of Wood-Preservative Treatments on Mechanical Properties of E-Glass/Phenolic Pultruded Composite Reinforcement for Wood, C. Tascioglu, B. Goodell, and R. Lopez-Anido, 11/12:53-61 (No. 9376).

Effects of Zinc Borate on the Properties of Medium Density Fiberboard, K. Tsunoda, H. Watanabe, K. Fukuda, and K. Hagio, 11/12:62-65 (No. 9361).

Fungal Susceptibility of Interior Commercial Building Panels, P.E. Laks, D.L. Richter, and G.M. Larkin, 5:41-44 (No. 9262).

How to Analyze Strand Alignment of Oriented Strandboard, W. Xu, 4:48-52 (No. 9270).

Manual Strand Orientation as a Means of Improving the Flexural Properties of Wood-Wool Cement Boards in the Philippines, R.J. Cabangon, R.B. Cunningham, and P.D. Evans, 4:53-59 (No. 9272).

Manufacturing Particleboard From Eastern Redcedar, S. Hiziroglu, R.B. Holcomb, and Q. Wu, 7/8:72-76 (No. 9295).

A Model of the Effect of Fines Content on the Strength Properties of Oriented Strand Wood Composites, D. Barnes, 5:55-60 (No. 9263).

A Model of the Effect of Orienter Design and Operating Variables on the Mean Angular Deviation of Oriented Wood Strands, D. Barnes, 7/8:63-71 (No. 9293).

A Model of the Effect of Strand Angle and Grain Angle on the Strength Properties of Oriented Veneer and Strand Wood Composites, D. Barnes, 4:39-47 (No. 9259).

Monitoring *in-situ* Density Change for In-Process Measurement and Control of Hot Pressing, S. Wang and P.M. Winistorfer, 7/8:77-82 (No. 9315).

Orientation of OSB and Particleboard Strands for High-Strength Oriented Strand Lumber and Panel Products, D. Barnes, 9:31-39 (No. 9317).

Performance of Pyrolysis Oil-Based Wood Adhesives in OSB, F. Chan, B. Riedl, X.-M. Wang, X. Lu, C. Amen-Chen, and C. Roy, 4:31-38 (No. 9230).

Selected Properties of Hybrid Poplar Clear Wood and Composite Panels, J.J. Peters, D.A. Bender, M.P. Wolcott, and J.D. Johnson, 5:45-54 (No. 9258).

Theoretical Approach on Specific Surface Area of Wood Particles, P. Bekhta and S. Hiziroglu, 4:72-76 (No. 9254).

Volatile Organic Compound Emissions Arising From the Hot-Pressing of Mixed Hardwood Particleboard, T. Jiang, D.J. Gardner, and M.G.D. Baumann, 11/12:66-77 (No. 9351).

Volatile Organic Compound Emissions During Hot-Pressing of Southern Pine Particleboard: Panel Size Effects and Trade-Off Between Press Time and Temperature, W. Wang, D.J. Gardner, and M.G.D. Baumann, 4:24-30 (No. 9261).

Wood Particle Size Affects the Decay Resistance of Wood Fiber/Thermoplastic Composites, S.A. Verhey and P.E. Laks, 11/12:78-81 (No. 9381).

DETERIORATION/DEGRADATION AND PRESERVATION

Comparison of Fixation Rates on Earlywood, Latewood, Sapwood, and Heartwood of CCA-Treated Douglas-fir, Southern Pine, and Eastern Larch, A. Guo, P.A. Cooper, Y.T. Ung, and J.N.R. Ruddick, 5:77-80 (No. 9292).

Comparison of Strength Properties and Failure Characteristics Between Fire-Retardant-Treated and Untreated Roof Framing Lumber After Long-Term Exposure: A South Carolina Case Study, D.A. Hodgin and A.W.C. Lee, 6:91-94 (No. 9232).

Comparisons of Interlaboratory Swellometer Testing of Two Water-Repellent Preservative Formulations for Millwork, E.L. Schmidt, T.P. Murphy, C.N. Cheeks, A.S. Ross, T.S. Chiu, and R.S. Williams, 3:82-84 (No. 9222).

Development and Application of Colorimetric Microassay for Determining Boron-

2002 *FPJ* SUBJECT AND AUTHOR INDEX

All of the articles in the 2002 *Forest Products Journal*, volume 52, are listed both by subject and by author. Reprints of most articles are available at $6 each. Bulk rates are also available. Please give reprint numbers when ordering. When printer-quality reprints are no longer available, photocopies can be ordered at 50 cents per page. All orders are subject to a $6 minimum charge plus $5 handling charge per order. There is a charge of $6 for a copy of the 2002 *FPJ* Subject and Author Index.

ADHESIVES/ADHESION

Effects of Treatment Methods on Relative Reactivity of BioMass Extracts Toward Formaldehyde, C.-M. Chen and L.C.-Y. Hsu, 2:92-99 (No. 9210).

Performance of Pyrolysis Oil-Based Wood Adhesives in OSB, F. Chan, B. Riedl, X.-M. Wang, X. Lu, C. Amen-Chen, and C. Roy, 4:31-38 (No. 9230).

AIR AND WATER QUALITY

Environmental Tradeoffs: Life Cycle Approach to Evaluate the Burdens and Benefits of Emission Control Systems in the Wood Panel Industry, B. Sauer, W. Franklin, R. Miner, D. Word, and B. Upton, 3:50-59 (No. 9408).

Volatile Organic Compound Emissions During Hot-Pressing of Southern Pine Particleboard: Panel Size Effects and Trade-Off Between Press Time and Temperature, W. Wang, D.J. Gardner, and M.G.D. Baumann, 4:24-30 (No. 9261).

ANATOMY AND QUALITY

Selected Properties of Hybrid Poplar Clear Wood and Composite Panels, J.J. Peters, D.A. Bender, M.P. Wolcott, and J.D. Johnson, 5:45-54 (No. 9258).

Volume Recovery, Grade Yield, and Properties of Lumber From Young-Growth Sitka Spruce and Western Hemlock in Southeast Alaska, G.A. Christiansen, K.R. Julin, R.J. Ross, and S. Willits, 5:81-87 (No. 9226).

CHEMISTRY AND CHEMICAL MODIFICATION

Effect of Glycol on Movement of Borate From Fused Borate Rods, C.M. Freitag and J.J. Morrell, 6:68-74 (No. 9269).

COMPOSITES AND ENGINEERED PRODUCTS

Demonstration Building Constructed With Round Mortise and Tenon Joints and Salvage Material From Small-Diameter Tree Stems, C. Eckelman, H. Akcay, R. Leavitt, and E. Haviarova, 11/12:82-86 (No. 9331).

Durability of an Extruded HDPE/Wood Composite, D.E. Pendleton, T.A. Hoffard, T. Adcock, B. Woodward, and M.P. Wolcott, 6:21-27 (No. 9278).

Effect of Cement/Wood Ratio on the Properties of Cement-Bonded Particleboard Using CCA-Treated Wood Removed From Service, Y. Zhou and D.P. Kamdem, 3:77-81 (No. 9257).

The Effect of Lab-Made Flakes on Physical and Mechanical Property Variability of Laboratory Flakeboard, C.J. Moriarty, 2:69-73 (No. 9165).

Effect of Log Storage on Structural Veneer Processing, R. Shmulsky, 4:82-84 (No. 9233).

Effects of Wood-Preservative Treatments on Mechanical Properties of E-Glass/Phenolic Pultruded Composite Reinforcement for Wood, C. Tascioglu, B. Goodell, and R. Lopez-Anido, 11/12:53-61 (No. 9376).

Effects of Zinc Borate on the Properties of Medium Density Fiberboard, K. Tsunoda, H. Watanabe, K. Fukuda, and K. Hagio, 11/12:62-65 (No. 9361).

Fungal Susceptibility of Interior Commercial Building Panels, P.E. Laks, D.L. Richter, and G.M. Larkin, 5:41-44 (No. 9262).

How to Analyze Strand Alignment of Oriented Strandboard, W. Xu, 4:48-52 (No. 9270).

Manual Strand Orientation as a Means of Improving the Flexural Properties of Wood-Wool Cement Boards in the Philippines, R.J. Cabangon, R.B. Cunningham, and P.D. Evans, 4:53-59 (No. 9272).

Manufacturing Particleboard From Eastern Redcedar, S. Hiziroglu, R.B. Holcomb, and Q. Wu, 7/8:72-76 (No. 9295).

A Model of the Effect of Fines Content on the Strength Properties of Oriented Strand Wood Composites, D. Barnes, 5:55-60 (No. 9263).

A Model of the Effect of Orienter Design and Operating Variables on the Mean Angular Deviation of Oriented Wood Strands, D. Barnes, 7/8:63-71 (No. 9293).

A Model of the Effect of Strand Angle and Grain Angle on the Strength Properties of Oriented Veneer and Strand Wood Composites, D. Barnes, 4:39-47 (No. 9259).

Monitoring *in-situ* Density Change for In-Process Measurement and Control of Hot Pressing, S. Wang and P.M. Winistorfer, 7/8:77-82 (No. 9315).

Orientation of OSB and Particleboard Strands for High-Strength Oriented Strand Lumber and Panel Products, D. Barnes, 9:31-39 (No. 9317).

Performance of Pyrolysis Oil-Based Wood Adhesives in OSB, F. Chan, B. Riedl, X.-M. Wang, X. Lu, C. Amen-Chen, and C. Roy, 4:31-38 (No. 9230).

Selected Properties of Hybrid Poplar Clear Wood and Composite Panels, J.J. Peters, D.A. Bender, M.P. Wolcott, and J.D. Johnson, 5:45-54 (No. 9258).

Theoretical Approach on Specific Surface Area of Wood Particles, P. Bekhta and S. Hiziroglu, 4:72-76 (No. 9254).

Volatile Organic Compound Emissions Arising From the Hot-Pressing of Mixed Hardwood Particleboard, T. Jiang, D.J. Gardner, and M.G.D. Baumann, 11/12:66-77 (No. 9351).

Volatile Organic Compound Emissions During Hot-Pressing of Southern Pine Particleboard: Panel Size Effects and Trade-Off Between Press Time and Temperature, W. Wang, D.J. Gardner, and M.G.D. Baumann, 4:24-30 (No. 9261).

Wood Particle Size Affects the Decay Resistance of Wood Fiber/Thermoplastic Composites, S.A. Verhey and P.E. Laks, 11/12:78-81 (No. 9381).

DETERIORATION/DEGRADATION AND PRESERVATION

Comparison of Fixation Rates on Earlywood, Latewood, Sapwood, and Heartwood of CCA-Treated Douglas-fir, Southern Pine, and Eastern Larch, A. Guo, P.A. Cooper, Y.T. Ung, and J.N.R. Ruddick, 5:77-80 (No. 9292).

Comparison of Strength Properties and Failure Characteristics Between Fire-Retardant-Treated and Untreated Roof Framing Lumber After Long-Term Exposure: A South Carolina Case Study, D.A. Hodgin and A.W.C. Lee, 6:91-94 (No. 9232).

Comparisons of Interlaboratory Swellometer Testing of Two Water-Repellent Preservative Formulations for Millwork, E.L. Schmidt, T.P. Murphy, C.N. Cheeks, A.S. Ross, T.S. Chiu, and R.S. Williams, 3:82-84 (No. 9222).

Development and Application of Colorimetric Microassay for Determining Boron-

Containing Compounds, S.N. Kartal and F. Green III, 6:75-79 (No. 9304).

Durability of an Extruded HDPE/Wood Composite, D.E. Pendleton, T.A. Hoffard, T. Adcock, B. Woodward, and M.P. Wolcott, 6:21-27 (No. 9278).

Effect of Cemented/Wood Ratio on the Properties of Cement/Bonded Particleboard Using CCA-Treated Wood Removed From Service, Y. Zhou and D.P. Kamdem, 3:77-81 (No. 9257).

Effect of Glycol on Movement of Borate From Fused Borate Rods, C.M. Freitag and J.J. Morrell, 6:68-74 (No. 9269).

Effect of Pre-Extraction by Different Solvent Systems on Leaching of CCA Components From Treated Appalachian Hardwoods, B.E. Dawson-Andoh, J.J. Slahor, L. Osborn, and L. McDonald, 10:62-66 (No. 9169).

Effects of Incising on Treatability and Leachability of CCA-C-Treated Eastern Hemlock, S.N. Kartal and S.T. Lebow, 2:44-48 (No. 9215).

Effects of Wood-Preservative Treatments on Mechanical Properties of E-Glass/Phenolic Pultruded Composite Reinforcement for Wood, C. Tascioglu, B. Goodell, and R. Lopez-Anido, 11/12:53-61 (No. 9376).

Effects of Zinc Borate on the Properties of Medium Density Fiberboard, K. Tsunoda, H. Watanabe, K. Fukuda, and K. Hagio, 11/12:62-65 (No. 9361).

Fungal Susceptibility of Interior Commercial Building Panels, P.E. Laks, D.L. Richter, and G.M. Larkin, 5:41-44 (No. 9262).

Mold Performance of Some Construction Products With and Without Borates, J.L. Fogel and J.D. Lloyd, 2:38-43 (No. 9213).

Movement of Boron and Fluoride From Rod Formations Into Douglas-fir Heartwood, R.G. Rhatigan, J.J. Morrell, and C.M. Freitag, 11/12:38-42 (No. 9325).

A New Fungicide Combination for Prevention of Kiln Brown Stain of White Pine, E.L. Schmidt, T.L. Highley, and M.H. Freeman, 11/12:51-52 (No. 9346).

Nondestructive Gamma Radiation Methods for Detection of Central Rot in Logs of Lenga (*Nothogagus pumilio*), J.T. Karsulovic, M.I. Dinator, and R. Morales, 11/12:87-93 (No. 9285).

Performance of Copper-Naphthenate-Treated Poles in Service, H.M. Barnes, J.A. Brient, M.H. Freeman, and C.N. Kerr, Jr., 4:60-63 (No. 9228).

Predicting Boron Diffusion in Wood From Surface Sorption, J.B. Ra, H.M. Barnes, and T.E. Conners, 10:67-70 (No. 9330).

Preventing Discoloration of Unseasoned Hem-fir and Douglas-fir Lumber With Selected Fungicide Formulations, J.J. Morrell, C.S. Love, and C.M. Freitag, 2:53-61 (No. 9177).

Properties of Laboratory-Made Plywood With Fipronil® Insecticide Added in the Resin Formulation, D.P. Kamdem, J. Hope, J. Oudenweyer, and M. Munro, 9:40-43 (No. 9313).

Relationships Between Mechanical Properties, Weight Loss, and Chemical Composition of Wood During Incipient Brown-Rot Decay, S.F. Curling, C.A. Clausen, and J.E. Winandy, 7/8:34-39 (No. 9308).

Treatability of Refractory Species With Amine and Amine/Ammoniacal Formulations of ACQ, P.I. Morris, S.M. McFarling, and A.R. Zahora, 10:37-42 (No. 9342).

Use of Anti-Stain Chemical Treatments by the Western U.S. Softwood Lumber Industry, 1999, R.C. Anderson, E. Hansen, and J. Morrell, 4:69-71 (No. 9265).

Wood Particle Size Affects the Decay Resistance of Wood Fiber/Thermoplastic Composites, S.A. Verhey and P.E. Laks, 11/12: 78-81 (No. 9381).

Wood Pole Purchasing, Inspection, and Maintenance: A Survey of Utility Practices, M. Mankowski, E. Hansen, and J.J. Morrell, 11/12:43-50 (No. 9336).

Drying and Storage

Effect of Air Velocity on Surface EMC in the Drying of Red Oak Lumber, R. Shmulsky, K. Kadir, and R. Erickson, 1:78-80 (No. 9202).

Effect of High-Temperature Drying on Bending and Shear Strengths of Western Hemlock Lumber, M. Thiam, M.R. Milota, and R.J. Leichti, 4:64-68 (No. 9152).

Effect of Log Storage on Structural Veneer Processing, R. Shmulsky, 4:82-84 (No. 9233).

Longitudinal Shrinkage, Kiln-Drying Defects, and Lumber Grade Recovery of Red Pine (*Pinus resinosa* Ait) From a 25-Year-Old Natural Stand and a 57-Year-Old Plantation, T. Deresse, R.K. Shepard, and R.W. Rice, 5:88-93 (No. 9180).

Wood Color Control During Kiln-Drying, B. Sundqvist, 2:30-37 (No. 9223).

Engineering and Mechanical Properties

Anisotropic Plasticity and the Notched Wood Shear Block, D.M. Moses and H.G.L. Prion, 6:43-54 (No. 9188).

Bending Strength and Stiffness Analysis of Butt-Jointed Glulam Beams for Residential Construction, A.B. Dansoh, K. Ueda, and T. Hirai, 9:82-87 (No. 9307).

Direct Withdrawal Strength of Multi-Staple Joints in Pine Plywood, J. Zhang, F. Quin, and B. Tackett, 5:61-66 (No. 9287).

Direct Withdrawal Strength of Single-Staple Joints in Pine Plywood, J. Zhang, F. Quin, B. Tackett, and S. Park, 2:86-91 (No. 9239).

Economic Feasibility of Producing Inside-Out Beams From Small-Diameter Logs, D.W. Patterson, R.A. Kluender, and J.E. Granskog, 1:23-26 (No. 9186).

Effect of Cross Holes on the Strength of Chair and Table Legs, C.A. Eckelman, Y.Z. Erdil, and E. Haviarova, 5:67-70 (No. 9370).

Effect of High-Temperature Drying on Bending and Shear Strengths of Western Hemlock Lumber, M. Thiam, M.R. Milota, and R.J. Leichti, 4:64-68 (No. 9152).

Effect of Loading and Vibration on Bending Properties of Pallet Deckboards, S.M. Connolly and A.W.C. Lee, 9:63-65 (No. 9434).

Effect of Metal Connector Plates on the Bending Strength of Solid Sawn Lumber and LVL: A Pilot Study, R. Gupta and B. Wagner, 10:71-74 (No. 9440).

Flexural Properties of Salvaged Dead Yellow-Cedar From Southeast Alaska, D.W. Green, K.A. McDonald, P.E. Hennon, J.W. Evans, and J.H. Stevens, 1:81-88 (No. 9168).

Holding Strength of Screws in Plywood and Oriented Strandboard, Y.Z. Erdil, J. Zhang, and C.A. Eckelman, 6:55-62 (No. 9277).

Lateral Holding Strength of Dowel Joints Constructed of Plywood and Oriented Strandboard, J. Zhang, Y.Z. Erdil, and C.A. Eckelman, 7/8:83-89 (No. 9300).

A Model of the Effect of Strand Angle and Grain Angle on the Strength Properties of Oriented Veneer and Strand Wood Composites, D. Barnes, 4:39-47 (No. 9259).

Nondestructive Evaluation Techniques for Assessing Modulus of Elasticity and Stiffness of Small-Diameter Logs, X. Wang, R.J. Ross, J.A. Mattson, J.R. Erickson, J.W. Forsman, E.A. Geske, and M.A. Wehr, 2:79-85 (No. 9216).

Pilot Study to Examine Use of Transverse Vibration Nondestructive Evaluation for Assessing Floor Systems, Z. Cai, R.J. Ross, M.O. Hunt, and L.A. Soltis, 1:89-93 (No. 9198).

Resistance of Southern Yellow Pine to Direct Withdrawal of Staples, J. Zhang, V. Yadama, and F. Quin, 9:75-81 (No. 9146).

Strength and Finishing Characteristics of Non-Processed and TASK™-Processed Hardwood Lumber, M.G. Sanders, T.L. Amburgey, and S.C. Kitchens, 9:60-62 (No. 9227).

Torsional Strength of Dowel Joints Constructed of Plywood and Oriented Strandboard, J. Zhang, Y.Z. Erdil, and C.A. Eckelman, 10:89-94 (No. 9328).

Transverse Vibration Test for Prediction of Stiffness and Strength Properties of Full Size *Eucalyptus grandis*, W.M.G. Burdzik and P.D. Nkwera, 6:63-67 (No. 9275).

Ultrasonic Inspection of Large Bridge Timbers, R. Emerson, D. Pollock, D. McLean, K. Fridley, R. Pellerin, and R. Ross, 9:88-95 (No. 9185).

Valuation of Destructively Tested Dimension Lumber From 25-, 30-, 35-, 40-, and 50-Year-Old Loblolly Pine Plantation Stands, E.J. Biblis and H.F. Carino, 2:74-78 (No. 9206).

Vibration Testing of Timber Floor Systems, L.A. Soltis, X. Wang, R.J. Ross, and M.O. Hunt, 10:75-81 (No. 9322).

Warp, MOE, and Grade of Structural Lumber Curve Sawn From Small-Diameter Douglas-fir Logs, F.G. Wagner, T.M. Gorman, K.L. Pratt, and C.E. Keegan, 1:27-31 (No. 9194).

Withdrawal and Bending Strength of Dowel Joints Constructed of Plywood and Oriented Strandboard, C.A. Eckelman, Y.Z. Erdil, and J. Zhang, 9:66-74 (No. 9323).

Withdrawal Strength of Punched Metal Tooth Plates in Red Oak End Grain, P.J. O'Regan and F.E. Woeste, 10:82-88 (No. 9329).

Finishing and Overlaying

Design and Evaluation of Furniture Finishing Systems, R.H. Melton, C.T. Culbreth, S.D. Roberts, and J.A. Joines, 7/8:27-33 (No. 9297).

Parametric Characterization of Peripheral Sanding, A.L. Carrano, J.B. Taylor, and R. Lemaster, 9:44-50 (No. 9288).

Strength and Finishing Characteristics of Non-Processed and TASK™-Processed Hardwood Lumber, M.G. Sanders, T.L. Amburgey, and S.C. Kitchens, 9:60-62 (No. 9227).

Furniture and Hardwood Veneer/Plywood

Color Grading of Beech Parquet Blocks by Using Spectral Data, P. Vienonen, A. Asikainen, and J. Eronen, 2:49-52 (No. 9201).

Effect of Cross Holes on the Strength of Chair and Table Legs, C.A. Eckelman, Y.Z. Erdil, and E. Haviarova, 5:67-70 (No. 9370).

The Effects of Lumber Length on Part Yields in Gang-Rip-First Rough Mills, P.C. Hamner, B.H. Bond, and J.K. Wiedenbeck, 5:71-76 (No. 9253).

Withdrawal and Bending Strength of Dowel Joints Constructed of Plywood and Oriented Strandboard, C.A. Eckelman, Y.Z. Erdil, and J. Zhang, 9:66-74 (No. 9323).

Lumber Production

The Effects of Lumber Length on Part Yields in Gang-Rip-First Rough Mills, P.C. Hamner, B.H. Bond, and J.K. Wiedenbeck, 5:71-76 (No. 9253).

Longitudinal Shrinkage, Kiln-Drying Defects, and Lumber Grade Recovery of Red Pine (*Pinus resinosa* Ait) From a 25-Year-Old Natural Stand and a 57-Year-Old Plantation, T. Deresse, R.K. Shepard, and R.W. Rice, 5:88-93 (No. 9180).

Marketing Strategies of Softwood Sawmills in Western North America, E. Hansen, J. Seppälä, and H. Juslin, 10:19-25 (9309).

A New Fungicide Combination for Prevention of Kiln Brown Stain of White Pine, E.L. Schmidt, T.L. Highley, and M.H. Freeman, 11/12:51-52 (No. 9346).

Quality Yield Capability of a Breakdown Sawing Process, J. Vuorilehto, 4:77-81 (No. 9268).

A Segmental Analysis of Current and Future Scanning and Optimizing Technology in the Hardwood Sawmill Industry, S.A. Bowe, R.L. Smith, D.E. Kline, and P.A. Araman, 3:68-76 (No. 9236).

Validation of the ROMI-RIP Rough Mill Simulator, E.R. Thomas and U. Buehlmann, 2:23-29 (No. 9200).

Volume Recovery, Grade Yield, and Properties of Lumber From Young-Growth Sitka Spruce and Western Hemlock in Southeast Alaska, G.A. Christiansen, K.R. Julin, R.J. Ross, and S. Willits, 5:81-87 (No. 9226).

Warp, MOE, and Grade of Structural Lumber Curve Sawn From Small-Diameter Douglas-fir Logs, F.G. Wagner, T.M. Gorman, K.L. Pratt, and C.E. Keegan, 1:27-31 (No. 9194).

Withdrawal and Bending Strength of Dowel Joints Constructed of Plywood and Oriented Strandboard, C.A. Eckelman, Y.Z. Erdil, and J. Zhang, 9:66-74 (No. 9323).

Marketing, Management, and Economics

An Analysis of Northern Hardwood Lumber Buyers' Use of Electronic Commerce, T.M. Smith, 2:62-68 (No. 9220).

A Comparative Study of Wood Highway Sound Barriers, S. Grgurevich, T. Boothby, H. Manbeck, C. Burroughs, S. Cegelka, C. bernecker, and M.A. Ritter, 3:35-43 (No. 9225).

Consumer Reactions to Environmental Labels for Forest Products: A Preliminary Look, M.E. Teisl, S. Peavey, F. Newman, J. Buono, and M. Hermann, 1:44-50 (No. 9205).

eBusiness Exchange Between Homecenter Buyers and Wood Products Suppliers, R.P. Vlosky and T. Westbrook, 1:38-43 (No. 9196).

Economic Feasibility of Producing Inside-Out Beams From Small-Diameter Logs, D.W. Patterson, R.A. Kluender, and J.E. Granskog, 1:23-26 (No. 9186).

An Exploratory Market Assessment of Wood Use in Japanese Residental Flooring and Windows, A. Wahl, R.A. Kozak, and D.H. Cohen, 1:51-58 (No. 9221).

An Exploratory Study of Internet Adoption by Primary Wood Products Manufacturers in the Western United States, R.P. Vlosky, T. Westbrook, and K. Poku, 6:35-42 (No. 9289).

First Impressions of Organizations and the Qualities Connoted by Wood in Interior Design, B.G. Ridoutt, R.D. Ball, and S.K. Killerby, 10:30-36 (No. 9345).

Flaws in an Assessment of Forest Resources in the Southern Appalachian Region, C. Schallau, P.E. Polzin, and M. Bennett, 3:44-49 (No. 9294).

Green Marketing of Softwood Lumber in Western North America and Nordic Europe, J. Kärnä, E. Hansen, H. Juslin, and J. Seppälä, 5:34-40 (No. 9280).

Homeowner Attitudes and Preferences for Building Materials With an Emphasis on Treated Wood Products, R.P. Vlosky and T.F. Shupe, 7/8:90-95 (No. 9318).

Internet Technologies in the Homecenter Industry, C.A. Roadcap, P.M. Smith, and J.H. Michael, 1:32-37 (No. 9179).

Marketing Strategies of Sofrwood Sawmills in Western North America, E. Hansen, J. Seppälä, and H. Juslin, 10:19-25 (9309).

Methodology for Evaluating Green Advertising of Forest Products in the United States: A Content Analysis, E.R. Wagner and E.N. Hansen, 4:17-23 (No. 9235).

A Profile of Timber Markets in the U.S. Southeast, R. Yin and J.P. Caulfield, 3:25-34 (No. 9203).

Segmenting Single-Family Home Builders on a Measure of Innovativeness, D. Fell, E.N. Hansen, and J. Punches, 6:28-34 (No. 9071).

Simulation of Forest Products Export Logistics: A Newsprint Paper Case Study, C. Gallis, 3:19-24 (No. 9266).

The Use of eBusiness in the Pacific Northwest Secondary Forest Products Industry, S.R. Shook, Y. Zhang, R. Braden, and J. Baldridge, 1:59-66 (No. 9209).

The Use of Incentives to Affect Response Rates for a Mail Survey of U.S. Marina Decision Makers, K.D. Bright and P.M. Smith, 10:26-29 (No. 9453).

Milling and Machining

A Benchmarking System for Evaluating the Profitability and Efficiency of Optimizing

Chop Saw Systems, T. Maness and D. Wong, 10:52-61 (No. 9339).

Investigation of Machine Parameters on the Surface Quality in Routing Soft Maple, P.H. Mitchell and R.L. Lemaster, 6:85-90 (No. 9291).

Longitudinal Shrinkage, Kiln-Drying Defects, and Lumber Grade Recovery of Red Pine (*Pinus resinosa* Ait) From a 25-Year-Old Natural Stand and a 57-Year-Old Plantation, T. Deresse, R.K. Shepard, and R.W. Rice, 5:88-93 (No. 9180).

Quality Yield Capability of a Breakdown Sawing Process, J. Vuorilehto, 4:77-81 (No. 9268).

A Segmental Analysis of Current and Future Scanning and Optimizing Technology in the Hardwood Sawmill Industry, S.A. Bowe, R.L. Smith, D.E. Kline, and P.A. Araman, 3:68-76 (No. 9236).

Tool Coatings for Wood Machining: Problems and Prospects, J.Y. Sheikh-Ahmad and T. Morita, 10:43-51 (No. 9354).

Validation of the ROMI-RIP Rough Mill Simulator, E.R. Thomas and U. Buehlmann, 2:23-29 (No. 9200).

Physics and Moisture Relations

Calibration of Moisture Meters for Southern Hardwoods, T.F. Shupe, Q. Wu, and I.D. Hartley, 7/8:59-62 (No. 9424).

Comparisons of Interlaboratory Swellometer Testing of Two Water-Repellent Preservative Formulations for Millwork, E.L. Schmidt, T.P. Murphy, C.N. Cheeks, A.S. Ross, T.S. Chiu, and R.S. Williams, 3:82-84 (No. 9222).

Development and Application of Colorimetric Microassay for Determining Boron-Containing Compounds, S.N. Kartal and F. Green III, 6:75-79 (No. 9304).

Theoretical Approach on Specific Surface Area of Wood Particles, P. Bekhta and S. Hiziroglu, 4:72-76 (No. 9254).

Wood Surface Feature Classification via Extended-Color Imagery, D.A. Butler, C.C. Brunner, and J.W. Funck, 6:80-84 (No. 9274).

Process Control/ Quality Control

A Benchmarking System for Evaluating the Profitability and Efficiency of Optimizing Chop Saw Systems, T. Maness and D. Wong, 10:52-61 (No. 9339).

Color Grading of Beech Parquet Blocks by Using Spectral Data, P. Vienonen, A. Asikainen, and J. Eronen, 2:49-52 (No. 9201).

Effect of Autocorrelated Data on Composite Panel Production Monitoring and Control: A Comparison of SPC Techniques, J.R. Noffsinger and R.B. Anderson, 3:60-67 (No. 9217).

Volatile Organic Compound Emissions Arising From the Hot-Pressing of Mixed Hardwood Particleboard, T. Jiang, D.J. Gardner, and M.G.D. Baumann, 11/12: 66-77 (No. 9351).

Volatile Organic Compound Emissions During Hot-Pressing of Southern Pine Particleboard: Panel Size Effects and Trade-Off Between Press Time and Temperature, W. Wang, D.J. Gardner, and M.G.D. Baumann, 4:24-30 (No. 9261).

Pulp and Paper

Simulation of Forest Products Export Logistics: A Newsprint Paper Case Study, C. Gallis, 3:19-24 (No. 9266).

Wood Chip Mill Harvest Volume and Area Impacts in North Carolina, J.D. Dodrill, F.W. Cubbage, R.H. Schaberg, and R.C. Abt, 11/12:29-37 (No. 9327).

Recycling and Residue Utilization

Flexural Properties of Salvaged Dead Yellow-Cedar From Southeast Alaska, D.W. Green, K.A. McDonald, P.E. Hennon, J.W. Evans, and J.H. Stevens, 1:81-88 (No. 9168).

The Wood Transportation and Resource Analysis System (WTRANS): An Analysis Tool to Assist Wood Residue Producers and Users, K. Jensen, J. Menard, B. English, W. Park, and B. Wilson, 5:27-33 (No. 9296).

Testing and Test Methodology

Nondestructive Gamma Radiation Methods for Detection of Central Rot in Logs of Lenga (*Nothogagus pumilio*), J.T. Karsulovic, M.I. Dinator, and R. Morales, 11/12:87-93 (No. 9285).

Ultrasonic Inspection of Large Bridge Timbers, R. Emerson, D. Pollock, D. McLean, K. Fridley, R. Pellerin, and R. Ross, 9:88-95 (No. 9185).

Timber Production and Harvesting

Delimbing Hybrid Poplar Prior to Processing With a Flail/Chipper, B.R. Hartsough, R. Spinelli, and S.J. Pottle, 4:85-93 (No. 9156).

Economic Desirability of Deferring the Harvesting of Loblolly Pine Plantation Timber for Structural Dimension Lumber Production, H.F. Carino and E.J. Biblis, 7/8: 52-58 (No. 9343).

Flaws in an Assessment of Forest Resources in the Southern Appalachian Region, C. Schallau, P.E. Polzin, and M. Bennett, 3:44-49 (No. 9294).

Harvest Cost Collection Approaches and Associated Equations for Restoration Treatments on National Forests, C.E. Keegan III, M.J. Niccolucci, C.E. Fiedler, J.G. Jones, and R.W. Regel, 7/8:96-99 (No. 9286).

Production Analysis of an Excavator-Based Harvester: A Case Study in Finnish Forest Operations, J. Wang and R. Haarlaa, 3:85-90 (No. 9249).

Productivity and Cost of CTL Harvesting of *Eucalyptus globulus* Stands Using Excavator-Based Harvesters, R. Spinelli, P.M.O. Owende, and S.M. Ward, 1:67-77 (No. 9172).

Timber Grade Distribution and Relative Stumpage Value of Mature Finnish *Betula pendula* and *B. pubescens* When Applying Different Bucking Principles, H. Heräjärvi and E. Verkasalo, 7/8:40-51 (No. 9311).

Wood Chip Mill Harvest Volume and Area Impacts in North Carolina, J.D. Dodrill, F.W. Cubbage, R.H. Schaberg, and R.C. Abt, 11/12:29-37 (No. 9327).

The Wood Transportation and Resource Analysis System (WTRANS): An Analysis Tool to Assist Wood Residue Producers and Users, K. Jensen, J. Menard, B. English, W. Park, and B. Wilson, 5:27-33 (No. 9296).

Wood and the Environment

Environmental Tradeoffs: Life Cycle Approach to Evaluate the Burdens and Benefits of Emission Control Systems in the Wood Panel Industry, B. Sauer, W. Franklin, R. Miner, D. Word, and B. Upton, 3:50-59 (No. 9408).

Increasing Long-Term Storage of Carbon Sequestered in Russian Softwood Logs Through Enhanced Lumber Recovery, W.E. Schlosser, J.H. Bassman, F.G. Wagner, and P.R. Wandschneider, 9:51-59 (No. 9320).

The Purchase Decision: Consumers and Environmentally Certified Wood Products, H. Bigsby and L.K. Ozanne, 7/8:100-105 (No. 9314).

Wood in the Interior Office Environment: Effects on Interpersonal Perception, B.G. Ridoutt, R.D. Ball, and S.K. Killerby, 9:23-30 (No. 9310).

Feature Articles

Advanced Engineered Wood Composites: Innovative Technologies for Maine's Forest Products Industry, R. Laverty, 11/12:18-26 (No. 9402).

Biomass for Heat and Power, R.L. Bain and R.P. Overend, 2:12-19 (No. 9395).

Durability Design for Wood Construction, G.C. Foliente, R.H. Leicester, C.-H. Wang, C. Mackenzie, and I. Cole, 1:10-19 (No. 9394).

International Forest Products Statistics Growing and Better Than Ever, E. Price, 5:12-23 (No. 9397).

The International Timber Trade, T. Peck, 9:10-19 (No. 9400).

Status and Trends in Global Forest Plantation Development, J. Carle, P. Vuorinen, and A. Del Lungo, 7/8:12-23 (No. 9399).

Wood-Framed Building Deconstruction: A Source of Lumber for Construction, B. Falk, 3:8-15 (No. 9396).

Wood-Plastic Composites in the United States: The Interfacing of Two Industries, C. Clemons, 6:10-18 (No. 9398).

Wood University: Online Engineered Wood Products Education, L. Hiles, 10:10-15 (No. 9401).

A

Abt, R.C., see Dodrill, J.D.

Adcock, T., see Pendleton, D.E.

Akcay, H., see Eckelman, C.

Amburgey, T.L., see Sanders, M.G.

Amen-Chen, C., see Chan, F.

Anderson, R.B., see Noffsinger, J.R.

Anderson, R.C., E. Hansen, and J. Morrell, Use of Anti-Stain Chemical Treatments by the Western U.S. Softwood Lumber Industry, 1999, 4:69-71 (No. 9265).

Araman, P.A., see Bowe, S.A.

Asikainen, A., see Vienonen, P.

B

Bain, R.L. and R.P. Overend, Biomass for Heat and Power, 2:12-19 (No. 9395).

Baldridge, J., see Shook, S.R.

Ball, R.D., see Ridoutt, B.G.

Barnes, D., A Model of the Effect of Fines Content on the Strength Properties of Oriented Strand Wood Composites, 5:55-60 (No. 9263).

Barnes, D., A Model of the Effect of Orienter Design and Operating Variables on the Mean Angular Deviation of Oriented Wood Strands, 7/8:63-71 (No. 9293).

Barnes, D., A Model of the Effect of Strand Angle and Grain Angle on the Strength Properties of Oriented Veneer and Strand Wood Composites, 4:39-47 (No. 9259).

Barnes, D., Orientation of OSB and Particleboard Strands for High-Strength Oriented Strand Lumber and Panel Products, 9:31-39 (No. 9317).

Barnes, H.M., J.A. Brient, M.H. Freeman, and C.N. Kerr, Jr., Performance of Copper-Naphthenate-Treated Poles in Service, 4:60-63 (No. 9228).

Barnes, H.M., see Ra, J.B.

Bassman, J.H., see Schlosser, W.E.

Baumann, M.G.D., see Jiang, T.

Baumann, M.G.D., see Wang, W.

Bekhta, P. and S. Hiziroglu, Theoretical Approach on Specific Surface Area of Wood Particles, 4:72-76 (No. 9254).

Bender, D.A., see Peters, J.J.

Bennett, M., see Schallau, C.

Bernecker, C., see Grgurevich, S.

Biblis, E.J. and H.F. Carino, Valuation of Destructively Tested Dimension Lumber From 25-, 30-, 35-, 40-, and 50-Year-Old Loblolly Pine Plantation Stands, 2:74-78 (No. 9206).

Biblis, E.J., see Carino, H.F.

Bigsby, H. and L.K. Ozanne, The Purchase Decision: Consumers and Environmentally Certified Wood Products, 7/8:100-105 (No. 9314).

Bond, B.H., see Hamner, P.C.

Boothby, T., see Grgurevich, S.

Bowe, S.A., R.L. Smith, D.E. Kline, and P.A. Araman, A Segmental Analysis of Current and Future Scanning and Optimizing Technology in the Hardwood Sawmill Industry, 3:68-76 (No. 9236).

Braden, R., see Shook, S.R.

Brient, J.A., see Barnes, H.M.

Bright, K.D. and P.M. Smith, The Use of Incentives to Affect Response Rates for a Mail Survey of U.S. Marina Decision Makers, 10:26-29 (No. 9453).

Brunner, C.C., see Butler, D.A.

Buehlmann, U., see Thomas, E.R.

Buono, J., see Teisl, M.E.

Burdzik, W.M.G. and P.D. Nkwera, Transverse Vibration Test for Prediction of Stiffness and Strength Properties of Full Size *Eucalyptus grandis*, 6:63-67 (No. 9275).

Burroughs, C., see Grgurevich, S.

Butler, D.A., C.C. Brunner, and J.W. Funck, Wood Surface Feature Classification via Extended-Color Imagery, 6:80-84 (No. 9274).

C

Cabangon, R.J., R.B. Cunningham, and P.D. Evans, Manual Strand Orientation as a Means of Improving the Flexural Properties of Wood-Wool Cement Boards in the Philippines, 4:53-59 (No. 9272).

Cai, Z., R.J. Ross, M.O. Hunt, and L.A. Soltis, Pilot Study to Examine Use of Transverse Vibration Nondestructive Evaluation for Assessing Floor Systems, 1:89-93 (No. 9198).

Carino, H.F. and E.J. Biblis, Economic Desirability of Deferring the Harvesting of Loblolly Pine Plantation Timber for Structural Dimension Lumber Production, 7/8: 52-58 (No. 9343).

Carino, H.F., see Biblis, E.J.

Carle, J., P. Vuorinen, and A. Del Lungo, Status and Trends in Global Forest Plantation Development, 7/8:12-23 (No. 9399).

Carrano, A.L., J.B. Taylor, and R. Lemaster, Parametric Characterization of Peripheral Sanding, 9:44-50 (No. 9288).

Caulfield, J.P., see Yin, R.

Cegelka, S., see Grgurevich, S.

Chan, F., B. Riedl, X.-M. Wang, X. Lu, C. Amen-Chen, and C. Roy, Performance of Pyrolysis Oil-Based Wood Adhesives in OSB, 4:31-38 (No. 9230).

Cheeks, C.N., see Schmidt, E.L.

Chen, C.-M. and L.C.-Y. Hsu, Effects of Treatment Methods on Relative Reactivity of BioMass Extracts Toward Formaldehyde, 2:92-99 (No. 9210).

Chiu, T.S., see Schmidt, E.L.

Christiansen, G.A., K.R. Julin, R.J. Ross, and S. Willits, Volume Recovery, Grade Yield, and Properties of Lumber From Young-Growth Sitka Spruce and Western Hemlock in Southeast Alaska, 5:81-87 (No. 9226).

Clausen, C.A., see Curling, S.F.

Clemons, C., Wood-Plastic Composites in the United States: The Interfacing of Two Industries, 6:10-18 (No. 9398).

Cohen, D.H., see Wahl, A.

Cole, I., see Foliente, G.C.

Conners, T.E., see Ra, J.B.

Connolly, S.M. and A.W.C. Lee, Effect of Loading and Vibration on Bending Properties of Pallet Deckboards, 9:63-65 (No. 9434).

Cooper, P.A., see Guo, A.

Cubbage, F.W., see Dodrill, J.D.

Culbreth, C.T., see Melton, R.H.

Cunningham, R.B., see Cabangon, R.J.

Curling, S.F., C.A. Clausen, and J.E. Winandy, Relationships Between Mechanical Properties, Weight Loss, and Chemical Composition of Wood During Incipient Brown-Rot Decay, 7/8:34-39 (No. 9308).

D

Dansoh, A.B., K. Ueda, and T. Hirai, Bending Strength and Stiffness Analysis of Butt-Jointed Glulam Beams for Residential Construction, 9:82-87 (No. 9307).

Dawson-Andoh, B.E., J.J. Slahor, L. Osborn, and L. McDonald, Effect of Pre-Extraction by Different Solvent Systems on Leaching of CCA Components From Treated Appalachian Hardwoods, 10:62-66 (No. 9169).

Del Lungo, A., see Carle, J.

Deresse, T., R.K. Shepard, and R.W. Rice, Longitudinal Shrinkage, Kiln-Drying Defects, and Lumber Grade Recovery of Red Pine (*Pinus resinosa* Ait) From a 25-Year-Old Natural Stand and a 57-Year-Old Plantation, 5:88-93 (No. 9180).

Dinator, M.I., see Karsulovic, J.T.

Dodrill, J.D., F.W. Cubbage, R.H. Schaberg, and R.C. Abt, Wood Chip Mill Harvest Volume and Area Impacts in North Carolina, 11/12:29-37 (No. 9327).

E

Eckelman, C., H. Akcay, R. Leavitt, and E. Haviarova, Demonstration Building Constructed With Round Mortise and Tenon Joints and Salvage Material From Small-Diameter Tree Stems, 11/12:82-86 (No. 9331).

Eckelman, C.A., Y.Z. Erdil, and E. Haviarova, Effect of Cross Holes on the Strength of Chair and Table Legs, 5:67-70 (No. 9370).

Eckelman, C.A., Y.Z. Erdil, and J. Zhang, Withdrawal and Bending Strength of Dowel Joints Constructed of Plywood and Oriented Strandboard, 9:66-74 (No. 9323).

Eckelman, C.A., see Erdil, Y.Z.

Eckelman, C.A., see Zhang, J.

Emerson, R., D. Pollock, D. McLean, K. Fridley, R. Pellerin, and R. Ross, Ultrasonic Inspection of Large Bridge Timbers, 9:88-95 (No. 9185).

English, B., see Jensen, K.

Erdil, Y.Z., J. Zhang, and C.A. Eckelman, Holding Strength of Screws in Plywood and Oriented Strandboard, 6:55-62 (No. 9277).

Erdil, Y.Z., see Eckelman, C.A.

Erdil, Y.Z., see Zhang, J.

Erickson, J.R., see Wang, X.

Erickson, R., see Shmulsky, R.

Eronen, J., see Vienonen, P.

Evans, J.W., see Green, D.W.

Evans, P.D., see Cabangon, R.J.

F

Falk, B., Wood-Framed Building Deconstruction: A Source of Lumber for Construction, 3:8-15 (No. 9396).

Fell, D., E.N. Hansen, and J. Punches, Segmenting Single-Family Home Builders on a Measure of Innovativeness, 6:28-34 (No. 9071).

Fiedler, C.E., see Keegan III, C.E.

Fogel, J.L. and J.D. Lloyd, Mold Performance of Some Construction Products With and Without Borates, 2:38-43 (No. 9213).

Foliente, G.C., R.H. Leicester, C.-H. Wang, C. Mackenzie, and I. Cole, Durability Design for Wood 1:10-19 (No. 9394).

Forsman, J.W., see Wang, X.

Franklin, W., see Sauer, B.

Freeman, M.H., see Barnes, H.M.

Freeman, M.H., see Schmidt, E.L.

Freitag, C.M., see Morrell, J.J.

Freitag, C.M., see Rhatigan, R.G.

Freitag, C.M. and J.J. Morrell, Effect of Glycol on Movement of Borate From Fused Borate Rods, 6:68-74 (No. 9269).

Fridley, K., see Emerson, R.

Fukuda, K., see Tsunoda, K.

Funck, J.W., see Butler, D.A.

G

Gallis, C., Simulation of Forest Products Export Logistics: A Newsprint Paper Case Study, 3:19-24 (No. 9266).

Gardner, D.J., see Jiang, T.

Gardner, D.J., see Wang, W.

Geske, E.A., see Wang, X.

Goodell, B., see Tascioglu, C.

Gorman, T.M., see Wagner, F.G.

Granskog, J.E., see Patterson, D.W.

Green, D.W., K.A. McDonald, P.E. Hennon, J.W. Evans, and J.H. Stevens, Flexural Properties of Salvaged Dead Yellow-Cedar From Southeast Alaska, 1:81-88 (No. 9168).

Green III, F., see Kartal, S.N.

Grgurevich, S., T. Boothby, H. Manbeck, C. Burroughs, S. Cegelka, C. Bernecker, and M.A. Ritter, A Comparative Study of Wood Highway Sound Barriers, 3:35-43 (No. 9225).

Guo, A., P.A. Cooper, Y.T. Ung, and J.N.R. Ruddick, Comparison of Fixation Rates on Earlywood, Latewood, Sapwood, and Heartwood of CCA-Treated Douglas-fir, Southern Pine, and Eastern Larch, 5:77-80 (No. 9292).

Gupta, R. and B. Wagner, Effect of Metal Connector Plates on the Bending Strength of Solid Sawn Lumber and LVL: A Pilot Study, 10:71-74 (No. 9440).

H

Haarlaa, R., see Wang, J.

Hagio, K., see Tsunoda, K.

Hamner, P.C., B.H. Bond, and J.K. Wiedenbeck, The Effects of Lumber Length on Part Yields in Gang-Rip-First Rough Mills, 5:71-76 (No. 9253).

Hansen, E., see Anderson, R.C.

Hansen, E., see Kärnä, J.

Hansen, E., see Mankowski, M.

Hansen, E., J. Seppälä, and H. Juslin, Marketing Strategies of Softwood Sawmills in Western North America, 10:19-25 (9309).

Hansen, E.N., see Fell, D.

Hansen, E.N., see Wagner, E.R.

Hartley, I.D., see Shupe, T.F.

Hartsough, B.R., R. Spinelli, and S.J. Pottle, Delimbing Hybrid Poplar Prior to Processing With a Flail/Chipper, 4:85-93 (No. 9156).

Haviarova, E., see Eckelman, C.

Haviarova, E., see Eckelman, C.A.

Hennon, P.E., see Green, D.W.

Heräjärvi, H. and E. Verkasalo, Timber Grade Distribution and Relative Stumpage Value of Mature Finnish *Betula pendula* and *B. pubescens* When Applying Different Bucking Principles, 7/8:40-51 (No. 9311).

Hermann, M., see Teisl, M.E.

Highley, T.L., see Schmidt, E.L.

Hiles, L., Wood University: Online Engineered Wood Products Education, 10:10-15 (No. 9401).

Hirai, T., see Dansoh, A.B.

Hiziroglu, S., R.B. Holcomb, and Q. Wu, Manufacturing Particleboard From Eastern Redcedar, 7/8:72-76 (No. 9295).

Hiziroglu, S., see Bekhta, P.

Hodgin, D.A. and A.W.C. Lee, Comparison of Strength Properties and Failure Characteristics Between Fire-Retardant-Treated and Untreated Roof Framing Lumber After Long-Term Exposure: A South Carolina Case Study, 6:91-94 (No. 9232).

Hoffard, T.A., see Pendleton, D.E.

Holcomb, R.B., see Hiziroglu, S.

Hope, J., see Kamdem, D.P.

Hsu, L.C.-Y., see Chen, C.-M.

Hunt, M.O., see Cai, Z.

Hunt, M.O., see Soltis, L.A.

J

Jensen, K., J. Menard, B. English, W. Park, and B. Wilson, The Wood Transportation and Resource Analysis System (WTRANS): An Analysis Tool to Assist Wood Residue Producers and Users, 5:27-33 (No. 9296).

Jiang, T., D.J. Gardner, and M.G.D. Baumann, Volatile Organic Compound Emissions Arising From the Hot-Pressing of Mixed Hardwood Particleboard, 11/12:66-77 (No. 9351).

Johnson, J.D., see Peters, J.J.

Joines, J.A., see Melton, R.H.

Jones, J.G., see Keegan III, C.E.

Julin, K.R., see Christiansen, G.A.

Juslin, H., see Hansen, E.

Juslin, H., see Kärnä, J.

K

Kadir, K., see Shmulsky, R.

Kamdem, D.P., J. Hope, J. Oudenweyer, and M. Munro, Properties of Laboratory-Made Plywood With Fipronil® Insecticide Added in the Resin Formulation, 9:40-43 (No. 9313).

Kamdem, D.P., see Zhou, Y.

Kärnä, J., E. Hansen, H. Juslin, and J. Seppälä, Green Marketing of Softwood Lumber in Western North America and Nordic Europe, 5:34-40 (No. 9280).

Karsulovic, J.T., M.I. Dinator, and R. Morales, Nondestructive Gamma Radiation Methods for Detection of Central Rot in Logs of Lenga (*Nothogagus pumilio*), 11/12: 87-93 (No. 9285).

Kartal, S.N. and F. Green III, Development and Application of Colorimetric Microassay for Determining Boron-Containing Compounds, 6:75-79 (No. 9304).

Kartal, S.N. and S.T. Lebow, Effects of Incising on Treatability and Leachability of CCA-C-Treated Eastern Hemlock, 2:44-48 (No. 9215).

Keegan, C.E., see Wagner, F.G.

Keegan III, C.E., M.J. Niccolucci, C.E. Fiedler, J.G. Jones, and R.W. Regel, Harvest Cost Collection Approaches and Associated Equations for Restoration Treatments on National Forests, 7/8:96-99 (No. 9286).

Kerr, C.N., Jr., see Barnes, H.M.

Killerby, S.K., see Ridoutt, B.G.

Kitchens, S.C., see Sanders, M.G.

Kline, D.E, see Bowe, S.A.

Kluender, R.A., see Patterson, D.W.

Kozak, R.A., see Wahl, A.

L

Laks, P.E., see Verhey, S.A.

Laks, P.E., D.L. Richter, and G.M. Larkin, Fungal Susceptibility of Interior Commercial Building Panels, 5:41-44 (No. 9262).

Larkin, G.M., see Laks, P.E.

Laverty, R., Advanced Engineered Wood Composites: Innovative Technologies for Maine's Forest Products Industry, 11/12: 18-26 (No. 9402).

Leavitt, R., see Eckelman, C.

Lebow, S.T., see Kartal, S.N.

Lee, A.W.C., see Connolly, S.M.

Lee, A.W.C., see Hodgin, D.A.

Leicester, R.H., see Foliente, G.C.

Leichti, R.J., see Thiam, M.

Lemaster, R., see Carrano, A.L.

Lemaster, R.L., see Mitchell, P.H.

Lloyd, J.D., see Fogel, J.L.

Lopez-Anido, R., see Tascioglu, C.

Love, C.S., see Morrell, J.J.

Lu, X., see Chan, F.

M

Mackenzie, C., see Foliente, G.C.

Manbeck, H., see Grgurevich, S.

Maness, T. and D. Wong, A Benchmarking System for Evaluating the Profitability and Efficiency of Optimizing Chop Saw Systems, 10:52-61 (No. 9339).

Mankowski, M., E. Hansen, and J. Morrell, Wood Pole Purchasing, Inspection, and Maintenance: A Survey of Utility Practices, 11/12:43-50 (No. 9336).

Mattson, J.A., see Wang, X.

McDonald, K.A., see Green, D.W.

McDonald, L., see Dawson-Andoh, B.E.

McFarling, S.M., see Morris, P.I.

McLean, D., see Emerson, R.

Melton, R.H., C.T. Culbreth, S.D. Roberts, and J.A. Joines, Design and Evaluation of Furniture Finishing Systems, 7/8:27-33 (No. 9297).

Menard, J., see Jensen, K.

Michael, J.H., see Roadcap, C.A.

Milota, M.R., see Thiam, M.

Miner, R., see Sauer, B.

Mitchell, P.H. and R.L. Lemaster, Investigation of Machine Parameters on the Surface Quality in Routing Soft Maple, 6:85-90 (No. 9291).

Morales, R., see Karsulovic, J.T.

Moriarty, C.J., The Effect of Lab-Made Flakes on Physical and Mechanical Property Variability of Laboratory Flakeboard, 2:69-73 (No. 9165).

Morita, T., see Sheikh-Ahmad, J.Y.

Morrell, J., see Anderson, R.C.

Morrell, J., see Mankowski, M.

Morrell, J.J., C.S. Love, and C.M. Freitag, Preventing Discoloration of Unseasoned Hem-fir and Douglas-fir Lumber With Selected Fungicide Formulations, 2:53-61 (No. 9177).

Morrell, J.J., see Freitag, C.M.

Morrell, J.J., see Rhatigan, R.G.

Morris, P.I., S.M. McFarling, and A.R. Zahora, Treatability of Refractory Species With Amine and Amine/Ammoniacal Formulations of ACQ, 10:37-42 (No. 9342).

Moses, D.M. and H.G.L. Prion, Anisotropic Plasticity and the Notched Wood Shear Block, 6:43-54 (No. 9188).

Munro, M., see Kamdem, D.P.

Murphy, T.P., see Schmidt, E.L.

N

Newman, F., see Teisl, M.E.

Niccolucci, M.J., see Keegan III, C.E.

Nkwera, P.D., see Burdzik, W.M.G.

Noffsinger, J.R. and R.B. Anderson, Effect of Autocorrelated Data on Composite Panel Production Monitoring and Control: A Comparison of SPC Techniques, 3:60-67 (No. 9217).

O

O'Regan, P.J. and F.E. Woeste, Withdrawal Strength of Punched Metal Tooth Plates in Red Oak End Grain, 10:82-88 (No. 9329).

Osborn, L., see Dawson-Andoh, B.E.

Oudenweyer, J., see Kamdem, D.P.

Overend, R.P., see Bain, R.L.

Owende, P.M.O., see Spinelli, R.

Ozanne, L.K., see Bigsby, H.

P

Park, S., see Zhang, J.

Park, W., see Jensen, K.

Patterson, D.W., R.A. Kluender, and J.E. Granskog, Economic Feasibility of Producing Inside-Out Beams From Small-Diameter Logs, 1:23-26 (No. 9186).

Peavey, S., see Teisl, M.E.

Peck,T., The International Timber Trade, 9:10-19 (No. 9400).

Pellerin, R., see Emerson, R.

Pendleton, D.E., T.A. Hoffard, T. Adcock, B. Woodward, and M.P. Wolcott, Durability of an Extruded HDPE/Wood Composite, 6:21-27 (No. 9278).

Peters, J.J., D.A. Bender, M.P. Wolcott, and J.D. Johnson, Selected Properties of Hybrid Poplar Clear Wood and Composite Panels, 5:45-54 (No. 9258).

Poku, K., see Vlosky, R.P.

Pollock, D., see Emerson, R.

Polzin, P.E., see Schallau, C.

Pottle, S.J., see Hartsough, B.R.

Pratt, K.L., see Wagner, F.G.

Price, E., International Forest Products Statistics Growing and Better Than Ever, 5:12-23 (No. 9397).

Prion, H.G.L., see Moses, D.M.

Punches,J., see Fell, D.

Q

Quin, F., see Zhang, J.

R

Ra, J.B., H.M. Barnes, and T.E. Conners, Predicting Boron Diffusion in Wood From Surface Sorption, 10:67-70 (No. 9330).

Regel, R.W., see Keegan III, C.E.

Rhatigan, R.G., J.J. Morrell, and C.M. Freitag, Movement of Boron and Fluoride From Rod Formations Into Douglas-fir Heartwood, 11/12:38-42 (No. 9325).

Rice, R.W., see Deresse, T.

Richter, D.L., see Laks, P.E.

Ridoutt, B.G., R.D. Ball, and S.K. Killerby, First Impressions of Organizations and the Qualities Connoted by Wood in Interior Design, 10:30-36 (No. 9345).

Ridoutt, B.G., R.D. Ball, and S.K. Killerby, Wood in the Interior Office Environment: Effects on Interpersonal Perception, 9:23-30 (No. 9310).

Riedl, B., see Chan, F.

Ritter, M.A., see Grgurevich, S.

Roadcap, C.A., P.M. Smith, and J.H. Michael, Internet Technologies in the Homecenter Industry, 1:32-37 (No. 9179).

Roberts, S.D., see Melton, R.H.

Ross, A.S., see Schmidt, E.L.

Ross, R., see Emerson, R.

Ross, R.J., see Cai, Z.

Ross, R.J., see Christiansen, G.A.

Ross, R.J., see Soltis, L.A.

Ross, R.J., see Wang, X.

Roy, C., see Chan, F.

Ruddick, J.N.R., see Guo, A.

S

Sanders, M.G., T.L. Amburgey, and S.C. Kitchens, Strength and Finishing Characteristics of Non-Processed and TASK™-Processed Hardwood Lumber, 9:60-62 (No. 9227).

Sauer, B., W. Franklin, R. Miner, D. Word, and B. Upton, Environmental Tradeoffs: Life Cycle Approach to Evaluate the Burdens and Benefits of Emission Control Systems in the Wood Panel Industry, 3:50-59 (No. 9408).

Schaberg, R.H., see Dodrill, J.D.

Schallau, C., P.E. Polzin, and M. Bennett, Flaws in an Assessment of Forest Resources in the Southern Appalachian Region, 3:44-49 (No. 9294).

Schlosser, W.E., J.H. Bassman, F.G. Wagner, and P.R. Wandschneider, Increasing Long-Term Storage of Carbon Sequestered in Russian Softwood Logs Through Enhanced Lumber Recovery, 9:51-59 (No. 9320).

Schmidt, E.L., T.L. Highley, and M.H. Freeman, A New Fungicide Combination for Prevention of Kiln Brown Stain of White Pine, 11/12:51-52 (No. 9346).

Schmidt, E.L., T.P. Murphy, C.N. Cheeks, A.S. Ross, T.S. Chiu, and R.S. Williams, Comparisons of Interlaboratory Swellometer Testing of Two Water-Repellent Preservative Formulations for Millwork, 3:82-84 (No. 9222).

Seppälä, J., see Hansen, E.

Seppälä, J., see Kärnä, J.

Sheikh-Ahmad, J.Y. and T. Morita, Tool Coatings for Wood Machining: Problems and Prospects, 10:43-51 (No. 9354).

Shepard, R.K., see Deresse, T.

Shmulsky, R., Effect of Log Storage on Structural Veneer Processing, 4:82-84 (No. 9233).

Shmulsky, R., K. Kadir, and R. Erickson, Effect of Air Velocity on Surface EMC in the Drying of Red Oak Lumber, 1:78-80 (No. 9202).

Shook, S.R., Y. Zhang, R. Braden, and J. Baldridge, The Use of eBusiness in the Pacific Northwest Secondary Forest Products Industry, 1:59-66 (No. 9209).

Shupe, T.F., Q. Wu, and I.D. Hartley, Calibration of Moisture Meters for Southern Hardwoods, 7/8:59-62 (No. 9424).

Shupe, T.F., see Vlosky, R.P.

Slahor, J.J., see Dawson-Andoh, B.E.

Smith, P.M., Bright, K.D.

Smith, P.M., see Roadcap, C.A.

Smith, R.L., see Bowe, S.A.

Smith, T.M., An Analysis of Northern Hardwood Lumber Buyers' Use of Electronic Commerce, 2:62-68 (No. 9220).

Soltis, L.A., X. Wang, R.J. Ross, and M.O. Hunt, Vibration Testing of Timber Floor Systems, 10:75-81 (No. 9322).

Soltis, L.A., see Cai, Z.

Spinelli, R., P.M.O. Owende, and S.M. Ward, Productivity and Cost of CTL Harvesting of *Eucalyptus globulus* Stands Using Excavator-Based Harvesters, 1:67-77 (No. 9172).

Spinelli, R., see Hartsough, B.R.

Stevens, J.H., see Green, D.W.

Sundqvist, B., Wood Color Control During Kiln-Drying, 2:30-37 (No. 9223).

T

Tackett, B., see Zhang, J.

Tascioglu, C., B. Goodell, and R. Lopez-Anido, Effects of Wood-Preservative Treatments on Mechanical Properties of E-Glass/Phenolic Pultruded Composite Reinforcement for Wood, 11/12:53-61 (No. 9376).

Taylor, J.B., see Carrano, A.L.

Teisl, M.E., S. Peavey, F. Newman, J. Buono, and M. Hermann, Consumer Reactions to Environmental Labels for Forest Products: A Preliminary Look, 1:44-50 (No. 9205).

Thiam, M., M.R. Milota, and R.J. Leichti, Effect of High-Temperature Drying on Bending and Shear Strengths of Western Hemlock Lumber, 4:64-68 (No. 9152).

Thomas, E.R. and U. Buehlmann, Validation of the ROMI-RIP Rough Mill Simulator, 2:23-29 (No. 9200).

Tsunoda, K., H. Watanabe, K. Fukuda, and K. Hagio, Effects of Zinc Borate on the Properties of Medium Density Fiberboard, 11/12:62-65 (No. 9361).

U

Ueda, K., see Dansoh, A.B.

Ung, Y.T., see Guo, A.

Upton, B., see Sauer, B.

V

Verhey, S.A. and P.E. Laks, Wood Particle Size Affects the Decay Resistance of Wood Fiber/Thermoplastic Composites, 11/12: 78-81 (No. 9381).

Verkasalo, E., see Heräjärvi, H.

Vienonen, P., A. Asikainen, and J. Eronen, Color Grading of Beech Parquet Blocks by Using Spectral Data, 2:49-52 (No. 9201).

Vlosky, R.P. and T.F. Shupe, Homeowner Attitudes and Preferences for Building Materials With an Emphasis on Treated Wood Products, 7/8:90-95 (No. 9318).

Vlosky, R.P. and T. Westbrook, eBusiness Exchange Between Homecenter Buyers and Wood Products Suppliers, 1:38-43 (No. 9196).

Vlosky, R.P., T. Westbrook, and K. Poku, An Exploratory Study of Internet Adoption by Primary Wood Products Manufacturers in the Western United States, 6:35-42 (No. 9289).

Vuorilehto, J., Quality Yield Capability of a Breakdown Sawing Process, 4:77-81 (No. 9268).

Vuorinen, P., see Carle, J.

W

Wagner, B., see Gupta, R.

Wagner, E.R. and E.N. Hansen, Methodology for Evaluating Green Advertising of Forest Products in the United States: A Content Analysis, 4:17-23 (No. 9235).

Wagner, F.G., T.M. Gorman, K.L. Pratt, and C.E. Keegan, Warp, MOE, and Grade of Structural Lumber Curve Sawn From Small-Diameter Douglas-fir Logs, 1:27-31 (No. 9194).

Wagner, F.G., see Schlosser, W.E.

Wahl, A., R.A. Kozak, and D.H. Cohen, An Exploratory Market Assessment of Wood Use in Japanese Residental Flooring and Windows, 1:51-58 (No. 9221).

Wandschneider, P.R., see Schlosser, W.E.

Wang, C.-H., see Foliente, G.C.

Wang, J. and R. Haarlaa, Production Analysis of an Excavator-Based Harvester: A Case Study in Finnish Forest Operations, 3:85-90 (No. 9249).

Wang, S. and P.M. Winistorfer, Monitoring *in-situ* Density Change for In-Process Measurement and Control of Hot Pressing, 7/8: 77-82 (No. 9315).

Wang, W., D.J. Gardner, and M.G.D. Baumann, Volatile Organic Compound Emissions During Hot-Pressing of Southern Pine Particleboard: Panel Size Effects and Trade-Off Between Press Time and Temperature, 4:24-30 (No. 9261).

Wang, X., R.J. Ross, J.A. Mattson, J.R. Erickson, J.W. Forsman, E.A. Geske, and M.A. Wehr, Nondestructive Evaluation Techniques for Assessing Modulus of Elasticity and Stiffness of Small-Diameter Logs, 2:79-85 (No. 9216).

Wang, X., see Soltis, L.A.

Wang X.-M., see Chan, F.

Ward, S.M., see Spinelli, R.

Watanabe, H., see Tsunoda, K.

Wehr, M.A., see Wang, X.

Westbrook, T., see Vlosky, R.P.

Wiedenbeck, J.K., see Hamner, P.C.

Williams, R.S., see Schmidt, E.L.

Willits, S., see Christiansen, G.A.

Wilson, B., see Jensen, K.

Winandy, J.E., see Curling, S.F.

Winistorfer, P.M., see Wang, S.

Woeste, F.E., see O'Regan, P.J.

Wolcott, M.P., see Pendleton, D.E.

Wolcott, M.P., see Peters, J.J.

Wong, D., see Maness, T.

Woodward, B., see Pendleton, D.E.

Word, D., see Sauer, B.

Wu, Q., see Hiziroglu, S.

Wu, Q., see Shupe, T.F.

X

Xu, W., How to Analyze Strand Alignment of Oriented Strandboard, 4:48-52 (No. 9270).

Y

Yadama, V., see Zhang, J.

Yin, R. and J.P. Caulfield, A Profile of Timber Markets in the U.S. Southeast, 3:25-34 (No. 9203).

Z

Zahora, A.R., see Morris, P.I.

Zhang, J., Y.Z. Erdil, and C.A. Eckelman, Lateral Holding Strength of Dowel Joints Constructed of Plywood and Oriented Strandboard, 7/8:83-89 (No. 9300).

Zhang, J., Y.Z. Erdil, and C.A. Eckelman, Torsional Strength of Dowel Joints Constructed of Plywood and Oriented Strandboard, 10:89-94 (No. 9328).

Zhang, J., F. Quin, and B. Tackett, Direct Withdrawal Strength of Multi-Staple Joints in Pine Plywood, 5:61-66 (No. 9287).

Zhang, J., F. Quin, B. Tackett, and S. Park, Direct Withdrawal Strength of Single-Staple Joints in Pine Plywood, 2:86-91 (No. 9239).

Zhang, J., V. Yadama, and F. Quin, Resistance of Southern Yellow Pine to Direct Withdrawal of Staples, 9:75-81 (No. 9146).

Zhang, J., see Eckelman, C.A.

Zhang, J., see Erdil, Y.Z.

Zhang, Y., see Shook, S.R.

Zhou, Y. and D.P. Kamdem, Effect of Cement/Wood Ratio on the Properties of Cement-Bonded Particleboard Using CCA-Treated Wood Removed From Service, 3:77-81 (No. 9257).